

PELLICOLE PER L'ISOLAMENTO TERMICO DEI VETRI

Pleolit[®] WG 70

WINDOW FILM PER GIARDINI D'INVERNO E VETRATE A PACCHETTO

DESCRIZIONE PRODOTTO

Le nostre pellicole brevettate Pleolit[®] possono essere applicate con posa interna nei vetri singoli, vetri doppi e laminati. Grazie alla loro elevata trasmissione della luce visibile e alle eccellenti proprietà di controllo solare, queste pellicole assicurano che il minor calore possibile venga perso durante i mesi più freddi. In altre parole, il tuo giardino d'inverno o la tua vetrata a pacchetto rimarrà più fresca in estate e più calda in inverno!



**INNOVATIVE
PRODUCT**



PROPRIETA'

- 52% di protezione solare
- 43% in meno di dispersione termica in inverno
- Applicabile su giardini d'inverno, vetrate a pacchetto e tanto altro
- Trasparente
- 10 anni di garanzia

PERFORMANCE SCHEDA TECNICA WG 70

Visible range (380 – 780 nm)	Film on glass	4 mm	10 mm
Trasmissione		73 %	71 %
Riflessione (lato pellicola)		12 %	11 %
Assorbimento		15 %	18 %
Solar range (300 – 2500 nm)			
Trasmissione		47 %	43 %
Riflessione (lato pellicola)		27 %	22 %
Assorbimento		26 %	35 %
Energia Solare Respinta TSER		49 %	52 %
Fattore Solare g		0,51	0,48
UV-range (280 - 380 nm) Respinta		>99%	>99%
Thermal range (5000 - 50.000 nm) Emissivita'		0,069	0,069

All data reported have been measured, calculated and reported in accordance with European Standard EN410, EN673 and EN12898 by Interuniversity INISMA Belgium. The technical results are subject to variations within industry standards. These test data only contain results that were obtained after the use of specific test procedures and standards. Extrapolation of the data of the sample or samples relating to the batch or lot from which data were obtained may not correlate and should be interpreted with caution. Group M.A.M. is not responsible for differences in quality, composition, appearance, performance, or other feature of a similar product produced by persons or under conditions over which Group M.A.M. has no control.



PROPRIETA' PELLICOLA

Spessore: 50 µm

Materiale: UV-stabilized super clear PET

Top coating: clear, inorganic and non-absorbing hardcoat

Adesivo: PS

Installazione: Inside

Garanzia: 10 contro distacco, rottura e demetallizzazione



UMISCREEN, PART OF GROUP MAM



Via della Pisana, 1338 00163 Roma (RM)
Numero Verde 800.198.028 www.michaelwindowfilm.it

UMISCREEN